Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.01.2026 Version number 3 (replaces version 2) Revision: 21.01.2026

*

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· Trade name: **Monument Filler**

· Article number: 47550

· UFI: 4QUD-P05M-Q00K-S0NR

· **1.2 Relevant identified uses of the substance or mixture and uses advised against** No further relevant information available.

· Application of the substance / the mixture Knife filler/ Surfacer
Polyester resin

· **1.3 Details of the supplier of the safety data sheet**

· Manufacturer/Supplier: AKEMI chemisch technische Spezialfabrik GmbH
Lechstrasse 28
D 90451 Nürnberg
Tel. +49(0)911-642960
Fax. +49(0)911-644456
e-mail info@akemi.de

· Further information obtainable from: Laboratory

· **1.4 Emergency telephone number:** Product Safety Department AKEMI chemisch technische Spezialfabrik GmbH
Tel. +49(0)911-64296-59
Reachable during the following office hours:
Monday – Thursday from 07:30 a.m. to 16:30 p.m.
Friday from 07:30 a.m. to 13:30 p.m.

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3	H226	Flammable liquid and vapour.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Repr. 2	H361d	Suspected of damaging the unborn child.
STOT RE 1	H372	Causes damage to the hearing organs through prolonged or repeated exposure.

· **2.2 Label elements**

· Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labelling: styrene

· Hazard statements
H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H361d Suspected of damaging the unborn child.
H372 Causes damage to the hearing organs through prolonged or repeated exposure.

· Precautionary statements
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.

(Contd. on page 2)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.01.2026 Version number 3 (replaces version 2) Revision: 21.01.2026

Trade name: Monument Filler

(Contd. of page 1)

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe vapours.
P280	Wear protective gloves / eye protection.
P302+P352	IF ON SKIN: Wash with plenty of water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P314	Get medical advice/attention if you feel unwell.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/ regional/national/international regulations.

· **2.3 Other hazards**
· Results of PBT and vPvB assessment
· PBT: Not applicable
· vPvB: Not applicable
· Determination of endocrine-disrupting properties: For information on endocrine disrupting properties see section 11.

*
SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**
· Description: Mixture: consisting of the following components.

· Dangerous components:

CAS: 14808-60-7 EINECS: 238-878-4	quartz substance with a Community workplace exposure limit	25-50%
CAS: 100-42-5 EINECS: 202-851-5 Index number: 601-026-00-0 Reg.nr.: 01-2119457861-32	styrene Flam. Liq. 3, H226 Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	12.5-25%
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46	ethyl acetate Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	<1%
CAS: 130-15-4 EINECS: 204-977-6 Reg.nr.: 01-2120760462-57	1,4-naphthoquinone Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 1, H330 Skin Corr. 1C, H314; Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1) Skin Sens. 1, H317; STOT SE 3, H335	<1%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· **4.1 Description of first aid measures**
· General information: Take affected persons out into the fresh air.
Position and transport stably in side position.
· After inhalation: Supply fresh air; consult doctor in case of complaints.
· After skin contact: If skin irritation continues, consult a doctor.
· After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
· After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.01.2026 Version number 3 (replaces version 2) Revision: 21.01.2026

Trade name: Monument Filler

(Contd. of page 2)

· **4.2 Most important symptoms and effects, both acute and delayed**

Breathing difficulty
Headache
Dizziness
Dizziness
Coughing
Profuse sweating
Nausea

· **4.3 Indication of any immediate medical attention and special treatment needed**

If swallowed, gastric irrigation with added, activated carbon.

SECTION 5: Firefighting measures

· **5.1 Extinguishing media**

· Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.

· For safety reasons unsuitable extinguishing agents:

Water
Water with full jet

· **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.
In case of fire, the following can be released:
Carbon monoxide (CO)
Under certain fire conditions, traces of other toxic gases cannot be excluded.

· **5.3 Advice for firefighters**

· Protective equipment:

Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.
Wear fully protective suit.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.
Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation
Keep away from ignition sources.
Use respiratory protective device against the effects of fumes/dust/aerosol.
Wear protective equipment. Keep unprotected persons away.

· **6.2 Environmental precautions:**

Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.01.2026 Version number 3 (replaces version 2) Revision: 21.01.2026

Trade name: Monument Filler

(Contd. of page 3)

See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling**

Keep receptacles tightly sealed.
Store in cool, dry place in tightly closed receptacles.
Keep away from heat and direct sunlight.
Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).
Use only in well ventilated areas.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

· **7.2 Conditions for safe storage, including any incompatibilities**

· Storage:

· Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.
Prevent any seepage into the ground.

· Information about storage in one common storage facility:

Store away from oxidising agents.
Store away from foodstuffs.

· Further information about storage conditions:

Store receptacle in a well ventilated area.
Protect from frost.
Keep container tightly sealed.

· Storage class: 3

· **7.3 Specific end use(s)** No further relevant information available.

*

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· Ingredients with limit values that require monitoring at the workplace:	
14808-60-7 quartz	
IOEL TWA	Long-term value: 0.05 mg/m³ Respirable dust
141-78-6 ethyl acetate	
IOELV	Short-term value: 1468 mg/m³, 400 ppm Long-term value: 734 mg/m³, 200 ppm

· DNELs		
100-42-5 styrene		
Oral	DNEL (Langzeit-wiederholt)	2.1 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	406 mg/kg bw/day (ARB)
		343 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	289-306 mg/m³ Air (ARB)
		174.25-182.75 mg/m³ Air (BEV)
	DNEL (Langzeit-wiederholt)	85 mg/m³ Air (ARB)
		10.2 mg/m³ Air (BEV)

(Contd. on page 5)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.01.2026 Version number 3 (replaces version 2) Revision: 21.01.2026

Trade name: Monument Filler

(Contd. of page 4)

141-78-6 ethyl acetate		
Oral	DNEL (Langzeit-wiederholt)	4.5 mg/kg bw/day (BEV)
Dermal	DNEL (Langzeit-wiederholt)	63 mg/kg bw/day (ARB)
		37 mg/kg bw/day (BEV)
Inhalative	DNEL (Kurzzeit-akut)	1,468 mg/m³ Air (ARB)
		734 mg/m³ Air (BEV)
	DNEL (Langzeit-wiederholt)	734 mg/m³ Air (ARB)
		367 mg/m³ Air (BEV)
130-15-4 1,4-naphthoquinone		
Inhalative	DNEL (Langzeit-wiederholt)	0.033 mg/m³ Air (ARB)

· PNECs

100-42-5 styrene	
PNEC (wässrig)	5 mg/l (KA)
	0.014 mg/l (MW)
	0.028 mg/l (SW)
	0.04 mg/l (WAS)
PNEC (fest)	0.2 mg/kg Trockengew (BO)
	0.307 mg/kg Trockengew (MWS)
	0.614 mg/kg Trockengew (SWS)
141-78-6 ethyl acetate	
PNEC (wässrig)	650 mg/l (KA)
	0.024 mg/l (MW)
	0.24 mg/l (SW)
	1.65 mg/l (WAS)
PNEC (fest)	0.148 mg/kg Trockengew (BO)
	0.115 mg/kg Trockengew (MWS)
	1.15 mg/kg Trockengew (SWS)
130-15-4 1,4-naphthoquinone	
PNEC (wässrig)	0.172 mg/l (KA)
	0.00261 mg/l (MW)
	0.0261 mg/l (SW)
PNEC (fest)	0.049 mg/kg Trockengew (BO)
	0.0321 mg/kg Trockengew (MWS)
	0.321 mg/kg Trockengew (SWS)

· Additional information: The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· Appropriate engineering controls No further data; see section 7.

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures:
Apply solvent resistant skin cream before starting work.
Use skin protection cream for skin protection.
Do not eat, drink, smoke or sniff while working.
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.

· Respiratory protection: Short term filter device:
Filter A/P2
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 6)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.01.2026 Version number 3 (replaces version 2) Revision: 21.01.2026

Trade name: Monument Filler

(Contd. of page 5)

· Hand protection

Preventive skin protection by use of skin-protecting agents is recommended.
After use of gloves apply skin-cleaning agents and skin cosmetics.
Skin protection agent recommendation for preventive skin shelter without use of protective gloves:
ARRETIL (http://www.stoko.com)
Skin protection agent recommendation for preventive skin shelter in application and combination of protective gloves:
STOKODERM (http://www.stoko.com)
The protection gloves to be used have to comply with the specifications of the directive 89/686/EC and the directive derived decree EN374, respectively, e.g. the above listed protection glove type. The mentioned permeation times´ data were generated and verified with material samples of the recommended protection glove type in the scope of laboratory anylyses of the company KCL GmbH in compliance with EN374.
This recommendation refers exclusively to the material safety data sheet referenced product delivered by Akemi and the indicated field of application. In case of product dilution or in case of mixture with different substances or chemicals, and in condition of EN374 deviation the producer of CE-approved protection gloves must be contacted for detailed information (e.g., KCL GmbH, Germany, 36124 Eichenzell, internet: http://www.kcl.de).
Skin protection recommendation for skin cleaning after product handling:
Kresto Classic (http://debstoko.com)
Skin protection agent recommendation for skin aftercare:
STOKO VITAN (http://www.stoko.com)

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Fluorocarbon rubber (Viton)
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

Value for the permeation: Level ≤ 480 min
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton)
Vitoject (KCL, Art_No. 890)
Butyl rubber, BR

· As protection from splashes gloves made of the following materials are suitable:

Fluorocarbon rubber (Viton)
Vitoject (KCL, Art_No. 890)
Butoject (KCL, Art_No. 897, 898)
Butyl rubber, BR

· Not suitable are gloves made of the following materials:

Natural rubber, NR
Chloroprene rubber, CR

(Contd. on page 7)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.01.2026 Version number 3 (replaces version 2) Revision: 21.01.2026

Trade name: Monument Filler

(Contd. of page 6)

Leather gloves
Rubber gloves
Strong material gloves
Neoprene gloves
Nitrile rubber, NBR

· Eye/face protection

Tightly sealed goggles

· Body protection: Protective work clothing

* **SECTION 9: Physical and chemical properties**

· **9.1 Information on basic physical and chemical properties**	
· General Information	
· Colour:	Grey
· Odour:	Specific type
· Odour threshold:	Not determined
· Melting point/freezing point:	Undetermined
· Boiling point or initial boiling point and boiling range	145 °C
· Flammability	Not applicable
· Lower and upper explosion limit	
· Lower:	1.2 Vol %
· Upper:	8.9 Vol %
· Flash point:	31 °C
· Auto-ignition temperature:	480 °C
· Decomposition temperature:	Not determined
· pH	Not determined Not applicable
· Viscosity:	
· Kinematic viscosity	Not determined
· Dynamic at 20 °C:	34,000 mPas
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined
· Vapour pressure at 20 °C:	6 hPa
· Density and/or relative density	
· Density at 20 °C:	1.59 g/cm³
· Relative density	Not determined
· Vapour density	Not determined
· Particle characteristics	112945-52-5 Hochdisperse Kieselsäure, synthetisches röntgenamorphes Siliciumdioxid: set including amorphous nanoforms; Number-based particle size distribution: d50: 2,5-50 nm
· **9.2 Other information**	
· Appearance:	
· Form:	Structurally viscous
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Solvent content:	
· Organic solvents:	20.0 %
· Solids content:	54.6 %

(Contd. on page 8)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.01.2026 Version number 3 (replaces version 2) Revision: 21.01.2026

Trade name: Monument Filler

(Contd. of page 7)

· Change in condition	
· Evaporation rate	Not determined

· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

· **10.1 Reactivity**	No further relevant information available.
· **10.2 Chemical stability**	
· Thermal decomposition / conditions to be avoided:	No decomposition if used and stored according to specifications.
· **10.3 Possibility of hazardous reactions**	Exothermic polymerisation. Reacts with peroxides and other radical forming substances. Reacts with strong alkali. Reacts with acids.
· **10.4 Conditions to avoid**	No further relevant information available.
· **10.5 Incompatible materials:**	No further relevant information available.
· **10.6 Hazardous decomposition products:**	No dangerous decomposition products known.

*
SECTION 11: Toxicological information

· **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)		
Inhalative	LC50/4 h	59.4 mg/l (rat)

14808-60-7 quartz		
Oral	LD50	500 mg/kg (rat)
100-42-5 styrene		
Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat) (OECD-Prüfrichtlinie 402)
Inhalative	LC50/4h	9,500 mg/m3 (mouse)

(Contd. on page 9)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.01.2026 Version number 3 (replaces version 2) Revision: 21.01.2026

Trade name: Monument Filler

(Contd. of page 8)

		11,800 mg/m3 (rat)
	LC50/4 h	11.8 mg/l (rat)
	NOAEC	4.34 mg/l (rat)
141-78-6 ethyl acetate		
Oral	LD50	4,100 mg/kg (mouse)
		5,620 mg/kg (rat)
		4,934 mg/kg (rabbit) (OECD 401)
	NOAEL-Werte	900 mg/kg (rat)
Dermal	LD50	>18,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC50	58 mg/l (rat)
	LC50/4 h	56 mg/l (rat)
	LC50/1h	200 mg/l (rat)
	LC50/8h	5.86 mg/l (rat)
	LC50/48h	333 mg/l (Leuciscus idus)
130-15-4 1,4-naphthoquinone		
Oral	LD50	124 mg/kg (rat)
	NOAEL-Werte	2 mg/kg (rat)
Dermal	LD50	300 mg/kg (ATE)
	LD50	202 mg/kg (rat)
Inhalative	LC50/4h	46 mg/m3 (rat)
	LC50/4 h	0.005 mg/l (ATE)

· Primary irritant effect:
· Skin corrosion/irritation — Causes skin irritation.
· Serious eye damage/irritation — Causes serious eye irritation.
· Respiratory or skin sensitisation — Based on available data, the classification criteria are not met.
· Germ cell mutagenicity — Based on available data, the classification criteria are not met.
· Carcinogenicity — Based on available data, the classification criteria are not met.
· Reproductive toxicity — Suspected of damaging the unborn child.
· STOT-single exposure — Based on available data, the classification criteria are not met.
· STOT-repeated exposure — Causes damage to the hearing organs through prolonged or repeated exposure.
· Aspiration hazard — Based on available data, the classification criteria are not met.

· **11.2 Information on other hazards**

· Endocrine disrupting properties
None of the ingredients is listed.

SECTION 12: Ecological information

· **12.1 Toxicity**

· Aquatic toxicity:	
100-42-5 styrene	
EC50/96h	6.3 mg/l (Pseudokirchneriella subcapitata)
EC50	500 mg/l (BES) (ISO Vorschrift 8192-1986 E)
	5.5 mg/l (Photobac. phosphoreum)
IC50/72h	4.9 mg/l (algae)
	1.4 mg/l (selenastrum capricornutum)
IC5/8d	>200 mg/l (Scenedesmus quadricauda)
EC10/16h	72 mg/l (pseudomonas putida)

(Contd. on page 10)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.01.2026 Version number 3 (replaces version 2) Revision: 21.01.2026

Trade name: Monument Filler

(Contd. of page 9)

EC50/16h	>72 mg/l (pseudomonas putida)
EC50/8d	>200 mg/l (Scenedesmus quadricauda)
EC50/72u	>1-<10 mg/l (algae)
EC20/0.5h	140 mg/l (BES) (OECD 209)
NOEC/21d	1.01 mg/l (daphnia magna)
EC10	0.28 mg/l (Pseudokirchneriella subcapitata) (EPA OTS 797.1050)
EC50/48h	0.56 mg/l (algae)
	3.3-7.4 mg/l (daphnia magna)
EC50/72h	0.46-4.3 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	>1-<10 mg/l (piscis)
	19.03-33.53 mg/l (lem)
	3.24-4.99 mg/l (pimephales promelas)
	6.75-14.5 mg/l (Pimephales promelas)
	58.75-95.32 mg/l (poecilia reticulata)
LC50/72h	4.9 mg/l (algae)
141-78-6 ethyl acetate	
EC50/24h	2,300-3,090 mg/l (daphnia magna)
EC50/96h	220 mg/l (Pimephales promelas)
EC10/18h	2,900 mg/l (pseudomonas putida)
EC50/48h	610 mg/l (daphnia magna) (DIN 38412)
	5,600 mg/l (Scenedesmus subspicatus)
IC50/48h	3,300 mg/l (Scenedesmus subspicatus)
LC 0	29.3 mg/l (rat)
NOELR/72h	>100 mg/l (Desmodesmus subspicatus) (OECD 201)
NOEC/21d	2.4 mg/l (daphnia magna) (DIN 38412 Part 11)
EC10	2,900 mg/l (pseudomonas putida)
EC50/48h	3,300 mg/l (Scenedesmus subspicatus)
EC50/72h	1,800-3,200 mg/l (selenastrum capricornutum)
LC50/96h	300-600 mg/l (Oncorhynchus mykiss)
	230 mg/l (Pimephales promelas)
130-15-4 1,4-naphthoquinone	
NOEC	0.011 mg/kg (algae)
EC50/48h	0.026 mg/l (daphnia magna)
EC50/72h	0.011 mg/l (algae)
	0.42 mg/l (Pseudokirchneriella subcapitata)
LC50/96h	0.045 mg/l (Oryzias latipes)

· **12.2 Persistence and degradability** No further relevant information available.
· **12.3 Bioaccumulative potential** No further relevant information available.
· **12.4 Mobility in soil** No further relevant information available.
· **12.5 Results of PBT and vPvB assessment**
· PBT: Not applicable
· vPvB: Not applicable
· **12.6 Endocrine disrupting properties** The product does not contain substances with endocrine disrupting properties.
· **12.7 Other adverse effects**
· Remark: Harmful to fish

(Contd. on page 11)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.01.2026 Version number 3 (replaces version 2) Revision: 21.01.2026

Trade name: Monument Filler

(Contd. of page 10)

· Additional ecological information:
· General notes: Do not allow product to reach ground water, water course or sewage system.
Harmful to aquatic organisms
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**
· Recommendation: Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue	
20 00 00	MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS
20 01 00	separately collected fractions (except 15 01)
20 01 27*	paint, inks, adhesives and resins containing hazardous substances

· Uncleaned packaging:
· Recommendation: Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.
· Recommended cleansing agents: Alcohol

*

SECTION 14: Transport information

· **14.1 UN number or ID number**
· ADR, IMDG, IATA: UN1866

· **14.2 UN proper shipping name**
· ADR: 1866 RESIN SOLUTION
· IMDG, IATA: RESIN SOLUTION

· **14.3 Transport hazard class(es)**

· ADR

· Class: 3 (F1) Flammable liquids.
· Label: 3

· IMDG, IATA

· Class: 3 Flammable liquids.
· Label: 3

· **14.4 Packing group**
· ADR, IMDG, IATA: III

· **14.5 Environmental hazards:**
· Marine pollutant: No

· **14.6 Special precautions for user**: Warning: Flammable liquids.
· Hazard identification number (Kemler code): 30

(Contd. on page 12)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.01.2026 Version number 3 (replaces version 2) Revision: 21.01.2026

Trade name: Monument Filler

(Contd. of page 11)

· EMS Number:	F-E,S-E
· Stowage Category	A
· **14.7 Maritime transport in bulk according to IMO instruments**	Not applicable
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· Remarks:	Without hardener component: no dangerous goods < 450 l
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Remarks:	Without hardener component: no dangerous goods < 450 l
· IATA	
· Remarks:	Without hardener component: 3/III UN 1866 Resin Solution
· UN "Model Regulation":	UN 1866 RESIN SOLUTION, 3, III

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

· Directive 2012/18/EU	
· Named dangerous substances - ANNEX I	None of the ingredients is listed.
· Seveso category	P5c FLAMMABLE LIQUIDS
· Qualifying quantity (tonnes) for the application of lower-tier requirements	5,000 t
· Qualifying quantity (tonnes) for the application of upper-tier requirements	50,000 t
· REGULATION (EC) No 1907/2006 ANNEX XVII	Conditions of restriction: 3

· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

· REGULATION (EU) 2019/1148

· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

(Contd. on page 13)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.01.2026 Version number 3 (replaces version 2) Revision: 21.01.2026

Trade name: Monument Filler

(Contd. of page 12)

· Regulation (EC) No 273/2004 on drug precursors
None of the ingredients is listed.

· Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors
None of the ingredients is listed.

· National regulations:

· Information about limitation of use: Employment restrictions concerning pregnant and lactating women must be observed.
Employment restrictions concerning juveniles must be observed.

· Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· Substances of very high concern (SVHC) according to REACH, Article 57
None of the ingredients is listed.

· VOC EU 318.3 g/l

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

· Department issuing SDS: Laboratory
· Date of previous version: 25.04.2024
· Version number of previous version: 2
· Abbreviations and acronyms:
RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO: International Civil Aviation Organisation
ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
SVHC: Substances of Very High Concern
vPvB: very Persistent and very Bioaccumulative
ATE: Acute toxicity estimate values
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 1: Acute toxicity – Category 1
Acute Tox. 4: Acute toxicity – Category 4
Skin Corr. 1C: Skin corrosion/irritation – Category 1C
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1
Repr. 2: Reproductive toxicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

(Contd. on page 14)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 21.01.2026 Version number 3 (replaces version 2) Revision: 21.01.2026

Trade name: Monument Filler

(Contd. of page 13)

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3