

Technical Data Sheet

Page 1 of 2

Properties:	<p>AKEMI® Lettering Primer Spray is a special primer.</p> <p>The product is characterized by the following properties:</p> <ul style="list-style-type: none">- improves the adhesion of lettering colours- fast drying- weather-resistant- economic, increases the filling power and thus reduces the consumption of lettering colours								
Application Area:	<p>AKEMI® Lettering Primer Spray is used to seal open-pored surfaces made of stone, concrete, terrazzo and many other materials. It also is used as a primer on hewn, milled or blasted letters on monuments, gravestones and sculptures prior to using AKEMI® Lettering Colours. AKEMI® Lettering Primer Spray increases the colour intensity and opacity of lettering colours. Suitable for indoors and outdoors.</p>								
Instructions for Use:	<ol style="list-style-type: none">1. The surface must be free of grease and dust, clean and dry.2. Cover up surfaces not to be treated and protect the surrounding area against spray mist.3. Shake the can vigorously until the balls rattle.4. Spray a thin layer cross-wise at a distance of approx. 25 cm, if necessary, repeat the process.5. After a drying time of approx. 20- 30 minutes (20°C), AKEMI® Lettering Colours can be used for painting.								
Special Notes:	<ul style="list-style-type: none">- For professional use only.- Do not use at too high temperatures or in intense sunlight because the primer would dry too quickly and does not run properly (formation of blooming). Optimum working temperature 15 - 25°C.- Drying is far better if the product is applied in several layers rather than one thick one.- It is not necessary to empty the spray nozzle when work is finished.- The durability of the AKEMI® Lettering Colour system is reduced on humid reverse stone surfaces. Sealing the back of the stone with AKEMI® Anti-Stain Coating 2015.- Areas which have been sprayed accidentally can be cleaned with an universal thinner (test of compatibility).- For proper waste disposal, the container must be completely emptied.- Recycling in accordance with the guidelines of EU Decision 97/129 EC on the Packaging Directive 94/62/EC.								
Technical Data:	<table><tr><td>Colour:</td><td>mat white</td></tr><tr><td>Density:</td><td>approx. 0.8 g/cm³</td></tr><tr><td>Coverage:</td><td>approx. 0.8 m²/spray can</td></tr><tr><td>Drying:</td><td>dust-dry after approx. 15 minutes (20°C) can be painted after approx. 20 - 30 minutes (20°C)</td></tr></table>	Colour:	mat white	Density:	approx. 0.8 g/cm ³	Coverage:	approx. 0.8 m ² /spray can	Drying:	dust-dry after approx. 15 minutes (20°C) can be painted after approx. 20 - 30 minutes (20°C)
Colour:	mat white								
Density:	approx. 0.8 g/cm ³								
Coverage:	approx. 0.8 m ² /spray can								
Drying:	dust-dry after approx. 15 minutes (20°C) can be painted after approx. 20 - 30 minutes (20°C)								
Storage:	<p>If stored in dry and cool condition (5-25°C/41-77°F) in its closed original container at least 60 months from production.</p>								
Health & Safety:	<p>Read Safety Data Sheet before handling or using this product.</p>								

TDS 10.25

Technical Data Sheet

Page 2 of 2

Important Notice:

The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trails of the product, in an inconspicuous area or fabrication of a sample piece.